

Automatic two-needle unit for attaching belt loops to denim trousers and classic trousers. The machine automatically proceeds to cut the belt loop, fold it and sew the reinforcing bartack to the jeans. Automatic position detection and removal of the belt joint as waste material. The automatic unit improves efficiency by 70% compared to 4 operators with the classic method.

- 2 fixed needles
- Sewing loops on classic jeans and trousers
- Cutting, folding and bartacking operation
- Automatic material waste
- Waste collector
- Touch screen display
- Automatic loop length adjustment
- Triangle or flat cut














@fuse_carlo_spa www.fuse.it fuse@fuse.it



254DBELT LOOPS ATTACHING

Belt Loops


Possibility to adjust the length and width of the reinforcement, the position of the end of the seam, the data of the waste material. Furthermore, the machine can automatically adjust the length of the loop via the motor without the operator have to do it manually.



Cutting Mode

The machine automatically proceeds to cut the belt loop, fold it and sew the reinforcing bartack to the jeans.

Double type of cut: triangle and flat.



Specs

Model	254D
Use	Belt loops attaching
Reinforce width	1.0mm-3.5mm
Reinforce lenght	5.0mm-22.0mm
Belt width	7mm-20mm
Reinforce lenght belt	45mm-75mm
Needle Type	DPx17#19#-#21
Voltage	AC220V
Air Pressure	0.5Mpa 1.8L/min
Weight	245Kg
Max Speed	2700rpm